


# Technical specifications

## FANCY 360 Herringbone

Art. N° 50

<b>Composition</b>	DIN 60001	100% Pure new wool (WV), Merino extra fine
<b>Usable width</b>	DIN EN 1773	Min. 150 cm
<b>Mass per unit area</b>	DIN EN 12127	240 g/m <sup>2</sup> (360 g/lm)
<b>Pilling resistance (Martindale)</b>	DIN EN ISO 12945-2	3-4 at 7.000 rubs
<b>Abrasion resistance (Martindale)</b>	DIN EN ISO 12947-2	20.000 abrasion cycles
<b>Colour fastness to rubbing, dry</b>	DIN EN ISO 105-X12	4-5
<b>Colour fastness to rubbing, wet</b>	DIN EN ISO 105-X12	4-5
<b>Colour fastness to light</b>	DIN EN ISO 105-B02	4-6 (depending on colour)
<b>Colour fastness to water</b>	DIN EN ISO 105-E01	4
<b>Colour fastness to perspiration</b>	DIN EN ISO 105-E04	4
<b>Piece length</b>	Ca. 50 meters	
<b>Recommended use</b>	Blazers, waistcoats, light jackets	
<b>Care instructions</b>		

 Note: Subject to change depending on technical upgrades. Values indicated without their specific tolerance levels are nominal values with a tolerance of  $\pm 5\%$ . All data presented is given to the best of our current knowledge for guidance purposes and is not legally binding. The technical data in the material data sheet is based on experience from current productions and does not constitute any quality agreement. This data refers to goods in ex-works condition without any processing or handling by the customer. The given data is informative only and merely serves as a guide. It will in no way release the customer from checking the suitability of the intended use, before processing and/or treatment.